

# Pacemark 3410 Printer Specifications

| Specification        | Details                                                                                                                                                                                               |
|----------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Printhead            | 9 pin                                                                                                                                                                                                 |
| Print speed @ 10 cpi | HSD: 550 cps<br>Utility: 417 cps<br>NLQ: 104 cps                                                                                                                                                      |
| Emulations           | Epson FX/IBM ProPrinter, co-resident Pacemark/Microline, by means of optional chip set                                                                                                                |
| Interface            | Parallel and RS232C serial, standard<br>Optional Twin-Ax/Co-Ax (3rd party - call 1-800-OKIDATA for information)                                                                                       |
| Graphics resolution  | 144 x 216 dpi maximum                                                                                                                                                                                 |
| Fonts                | NLQ: Courier, Gothic, Proportional<br>Draft: Utility, High Speed<br>Bar Code: UPC-A, UPC-E, EAN 8, EAN 13, Code 3 of 9, Interleaved 2 of 5                                                            |
| Buffer size          | 64K                                                                                                                                                                                                   |
| Reliability          | Mean Time Between Failures (MTBF): 8,000 hours at 25% duty cycle, 35% page density<br>Mean Time To Repair (MTTR): 15 minutes<br>Printhead life: 200 million characters average in 10 cpi utility mode |
| Paper specifications | Weight: 12 to 24 lb.<br>Thickness:<br>Top feed: 0.36 mm (0.014 inches) maximum<br>Bottom feed: 0.50 mm (0.020 inches) maximum                                                                         |

Recreated from the original Pacemark 3410 specifications reference image.